

CERAClick

			CeraClick
	Dimensions & thickness	EN ISO 10545-2	ca. 1203 × 603 × 14 mm
	Classification	UNI EN 14411 / ISO 13006	App. G B I a / Annex G B I a
	Total weight	EN 430	ca. 26000 g/m²
	Effect of castor chair	EN 425	suitable
	Reaction of fire	EN ISO 9239-1	Afl-s1
	Thermal resistance	EN 12524	0,05 m² K/W
	Dimensional stability	EN 434	< 0,02 %
	Residual indentation	EN 433	0,00 mm
	Lightfast	ISO 105	> 7
	Emissions value		in conformity with AgBB
	Swellness value 24h	EN 317	0% (waterproof)
	Locking strength	ISO 24334	> 500 kg/lfm – kg/m
	Reaction to static electricity	EN 1815	< 2,0 kV
	Temperature resistance		Resistant
	Slipperiness	DIN 51130:2014	R11
	Joint width		ca. 3 mm
	Impact sound reduction		16 dB
	Resistance to chemicals	EN ISO 10545-13	A-LA-HA
	Resistance to stains	EN ISO 10545/14	3 / 3 / 3
	Abraision resistance	EN ISO 10545/6	< 175 mm³
	Breakage resistance	EN ISO 10545-4	≥ 35 N/mm² (individual Min. 32 N/mm²) ≥ 1300 N
	Thermal expansion coefficient	EN ISO 10545/8	6,5 × 10 ⁻⁶ / °C